



**POLYMAT POTA – R or HM, 1.50mm**

**FASTENING**

NOTE: OPTIONAL  
 \* PROTECTION LAYER (GEOTEXTILE 200g/m<sup>2</sup>) IS RECOMMENDED FOR ROUGH AND UNEVEN SURFACE FINISH. OTHERWISE, THE PVC MEMBRANE CAN BE DIRECTLY APPLIED ON THE SUBSTRATE SURFACE.

**BITUMAT COMPANY LIMITED**  
 P.O. Box 7487, Dammam 31462, Kingdom of Saudi Arabia  
 Tel. No. (+966-13) 8121210 / 8121213  
 Fax No. (+966-13) 8121190  
 Google Earth Address: 2608 34327-6935  
 Website: www.bitumat.com

THIS DRAWING IS FOR ILLUSTRATIVE PURPOSES ONLY OF PROFILES SHOWN IN OUR OFFICIAL CATALOGUE. ALL PROFILES MUST BE VERIFIED AND APPROVED BY THE AUTHORIZED REPRESENTATIVE OF BITUMAT BEFORE ANY ACTION IS TAKEN.

DRAWING TITLE  
**POLYMAT PVC - SINGLE PLY**  
**POLYMAT POTA**  
**WATER TANK WATERPROOFING FASTENING**  
**(Horizontal + Vertical)**  
 SHEET CONTENTS: WATERPROOFING SYSTEM DETAILS

REMARKS

REVISION		DRAWN BY :
0.0	DATE :	CHECKED BY :
		DATE :
		REF. NO.

DWG. No.  
**MS.05.01-03**